

ZX16-H-SOi

Hanging ▲ ZX16-H Series



Characteristics



Listed



Standard



SORAA compatible

- Wet/Dry location rated. • Integral Thermal dissipation for the SORAA MR16 LED in a compact, aesthetic fixture. US patented. • Reduces LED junction temperature by a tested 20-30C(68-86F) • Allows entire catalogue of SORAA LED MR16 lamps to be used in an enclosed fixture without sacrificing the performance of the light bulb. • Utilizes one cable for both support and power for a clean installation. No messy coordination trying to manage a separate hanging wire rope and power cable. • For lamp selections, please refer to <http://www.soraa.com/products/specs-GU5.3-US> • Fixture comes with 5 ft whip

Technical Data

Material	Housing/Cap/Stem - Machined silicone magnesium aluminum alloy (6061-T6) resistant to corrosion Stainless steel (SS304) hardware
Lamp	Soraa MR16
Dimmability	MLV, ELV
Hoods	B
Socket	Bi-pin, GX5.3
Voltage	12V
Wattage	Max. SORAA 11.5W
Color Temp	2.7K, 3K, 4K
Power Supply	Requires remote step down transformer

PROJECT

FIXTURE TYPE

Ordering Guide

Series	ZX16-H-SOi
Hoods	B
Glare Shields (optional)	GSL GSA GSS
Voltage	12V
Wattage	Max. SORAA 11.5W
Lamp	Soraa MR16
Socket	Bi-pin GX5.3
Color Temp	2.7K 3K 4K
Finish	BK (black) BZ (bronze) WT (white) ABK (anodized black) ACL (anodized clear) CC (custom)

