

# ZX16-H-SOi

Hanging ▲ ZX16-H Series



PROJECT \_\_\_\_\_

FIXTURE TYPE \_\_\_\_\_

## Characteristics



Listed



Standard



Sora compatible

- Wet/Dry location rated.
- Integral Thermal dissipation for the SORAA MR16 LED in a compact, aesthetic fixture. US patented.
- Reduces LED junction temperature by a tested 20-30C(68-86F)
- Allows entire catalogue of SORAA LED MR16 lamps to be used in an enclosed fixture without sacrificing the performance of the light bulb.
- For lamp selections, please refer to <http://www.soraa.com/products/specs-GU5.3-US>
- Fixture comes with 5 ft whip

## Technical Data

<b>Material</b>	Housing/Cap/Stem - Machined silicone magnesium aluminum alloy (6061-T6) resistant to corrosion Stainless steel (SS304) hardware
<b>Lamp</b>	Soraa MR16
<b>Dimmability</b>	MLV, ELV
<b>Hoods</b>	B
<b>Socket</b>	Bi-pin, GX5.3
<b>Voltage</b>	12V
<b>Wattage</b>	Max. SORAA 11.5W
<b>Color Temp</b>	2.7K, 3K, 4K
<b>Power Supply</b>	Requires remote step down transformer

## Ordering Guide

<b>Series</b>	ZX16-H-SOi
<b>Hoods</b>	B
<b>Glare Shields (optional)</b>	GSL GSA GSS
<b>Voltage</b>	12V
<b>Wattage</b>	Max. SORAA 11.5W
<b>Lamp</b>	Soraa MR16
<b>Socket</b>	Bi-pin GX5.3
<b>Color Temp</b>	2.7K 3K 4K
<b>Finish</b>	BK (black) BZ (bronze) WT (white) ABK (anodized black) ACL (anodized clear) CC (custom)

