



Guangdong Meide Testing Technology Co., Ltd.



TEST REPORT OF ANSI/IES LM-79-19

APPROVED METHOD FOR OPTICAL AND ELECTRICAL MEASUREMENTS OF SOLID-STATE LIGHTING PRODUCTS

Client..... : HK Lighting Group

Address..... : 3529 Old Conejo, Suite 118, Newbury Park, CA. USA

Test Model..... : PATH-L-08L-SQ-2

Product Description : LED Luminaire

Brand Name..... : HK Lighting Group

Testing Laboratory..... : Guangdong Meide Testing Technology Co., Ltd.

Address..... : 1st floor, B Area, Jinbaisheng Industrial Park, Headquarters 2 Road,
Songshan Lake Hi-tech Industrial Development Zone,Dongguan City,
Guangdong Pr., China.

Testing location..... : As above

Report No..... : CA2006443L 01001

Test Date..... : June.22,2020 - June.24,2020

Report Date..... : June.28,2020

Tested by:

Tim Qian/ Test Engineer

Checked by:

Luke Lei/ Project Engineer

Approved by:

Jessie Li/ Technical Manager

Note 1: The test data was only valid for the test sample(s).This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or use in part without prior written consent from Guangdong Meide Testing Technology Co., Ltd. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Note 2: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Guangdong Meide Testing Technology Co., Ltd.



1. Product Description for Equipment under Test(EUT)

The client submitted 1 sample of model PATH-L-08L-SQ-2. The sample was received on 2020-06-22, is in undamaged condition.

Model Tested:	PATH-L-08L-SQ-2
Manufacturer:	HK Lighting Group
Address:	3529 Old Conejo, Suite 118, Newbury Park, CA. USA
Product Type:	LED Luminaire
Rated Voltage/Frequency:	AC 12V 60Hz
Rated Power:	4W
Nominal CCT:	4000K
LED Manufacturer:	Nichia
LED Model No:	NVSL219BT-V1

2. Standards Used

- ANSI/IES LM-79-19: APPROVED METHOD: OPTICAL AND ELECTRICAL MEASUREMENTS OF SOLID-STATE LIGHTING PRODUCTS

3. Test equipment list

Test Equipment	Serial No	Model No	Calibration due date
Full-field Speed Goniophotometer	MD-E028	GO-R5000	2020/10/06
Digital Power Meter	MD-E001	PF2010	2020/10/06
AC Testing Power Source	MD-E002	DPS1060	2020/10/06
Total Spectral Radiant Flux Standard Lamp	MD-E007	D908S	2020/10/06

Statement of Traceability: Guangdong Meide Testing Technology Co., Ltd. attested that all calibration has been performed using suitable standards traceable to national primary standards and International System of Unit(SI).



Guangdong Meide Testing Technology Co., Ltd.



4. Test Method

Requirements of Ambient Condition

Product was tested with no seasoning. All stabilization and measurements were made in compliance with ANSI/IES LM-79-19. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at $25^{\circ}\text{C} \pm 1.2^{\circ}\text{C}$ during measurement. And relative humidity between 10% and 65%.

Goniophotometer System

The sample was tested according to the ANSI/IES LM-79-19.

Photometric parameters were measured using a type C goniophotometer and software. The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, Luminous efficacy, zonal flux were calculated from the software taken at 1° vertical intervals and 22.5° horizontal intervals. Photometric distance was more than five times of the Largest dimension of the test SSL product.



Guangdong Meide Testing Technology Co., Ltd.



5. Goniophotometer Test results

5.1 Test Data

Test Ambient Temperature	25.1℃	Test orientation	Downward
Operate time(Min.)	90	stabilization time(Min.)	60


Electrical Measurement

Input Voltage (V)	Frequency (Hz)	Input Current(A)	Power Factor	Power(W)
12.01	60.00	0.6161	0.6251	4.624

Photometric Measurement

Luminous Flux (lm)	Efficacy(lm/W)	I _{max} (cd)	Spacing Criteria (C0/180°)	Spacing Criteria (C90/270°)
263.375	56.96	100.9	1.25	1.36

5.2 LUMINOUS INTENSITY DISTRIBUTION DIAGRAM AND C0 PLANE ISOLUX DIAGRAM (UNIT:lx)




AVERAGE BEAM ANGLE(50%):110.2 DEG




Guangdong Meide Testing Technology Co., Ltd.



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT: lx)



AVERAGE BEAM ANGLE(10%):149.7 DEG



Guangdong Meide Testing Technology Co., Ltd.



5.3 ZONAL FLUX DIAGRAM

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	90.35	93.66	91.02	90.83	91.37	91.54	92.25	100.9	0- 10	8.940	8.940	3.39, 3.39
20	89.78	93.20	88.01	92.57	86.18	90.95	91.71	92.85	10- 20	26.05	34.99	13.3, 13.3
30	84.96	88.92	80.73	83.53	78.27	87.04	86.64	87.32	20- 30	40.80	75.79	28.8, 28.8
40	75.31	77.54	71.62	73.23	68.25	80.12	75.55	79.19	30- 40	50.16	126.0	47.8, 47.8
50	60.02	61.06	54.96	55.66	51.56	60.48	57.77	64.08	40- 50	51.83	177.8	67.5, 67.5
60	41.04	41.51	35.93	35.01	34.84	40.25	40.13	43.15	50- 60	44.16	221.9	84.3, 84.3
70	20.44	19.80	17.91	16.89	17.03	19.76	18.73	20.97	60- 70	28.77	250.7	95.2, 95.2
80	5.467	4.573	3.701	3.511	4.105	5.117	1.707	4.104	70- 80	11.45	262.2	99.5, 99.5
90	0	0	0	0	0	0	0	0	80- 90	1.224	263.4	100, 100
100	0	0	0	0	0	0	0	0	90-100	0	263.4	100, 100
110	0	0	0	0	0	0	0	0	100-110	0	263.4	100, 100
120	0	0	0	0	0	0	0	0	110-120	0	263.4	100, 100
130	0	0	0	0	0	0	0	0	120-130	0	263.4	100, 100
140	0	0	0	0	0	0	0	0	130-140	0	263.4	100, 100
150	0	0	0	0	0	0	0	0	140-150	0	263.4	100, 100
160	0	0	0	0	0	0	0	0	150-160	0	263.4	100, 100
170	0	0	0	0	0	0	0	0	160-170	0	263.4	100, 100
180	0	0	0	0	0	0	0	0	170-180	0	263.4	100, 100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 152.3 lm

%lum = 57.8%

%lamp = 57.8%


Conical surface Flux(120deg): 221.93 lm

%lum = 84.3%

%lamp = 84.3%



5.4 LUMINANCE LIMITATION CURVES






Guangdong Meide Testing Technology Co., Ltd.



5.5 CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.05	1.02	.98	1.03	.90	.97	.99	.96	.93	.95	.93	.91	.92	.90	.88	.86
2.0	.93	.86	.81	.91	.85	.80	.87	.82	.78	.84	.80	.76	.81	.78	.75	.73
3.0	.82	.74	.68	.80	.73	.67	.77	.71	.66	.74	.69	.65	.72	.68	.64	.62
4.0	.73	.64	.58	.71	.63	.57	.69	.62	.56	.66	.61	.56	.64	.59	.55	.53
5.0	.65	.56	.50	.64	.56	.49	.62	.54	.49	.60	.53	.48	.58	.52	.48	.46
6.0	.58	.50	.43	.57	.49	.43	.56	.48	.43	.54	.47	.42	.52	.47	.42	.40
7.0	.53	.44	.38	.52	.44	.38	.51	.43	.38	.49	.43	.38	.48	.42	.37	.35
8.0	.48	.40	.34	.48	.40	.34	.46	.39	.34	.45	.38	.34	.44	.38	.33	.32
9.0	.44	.36	.31	.44	.36	.31	.43	.35	.30	.41	.35	.30	.40	.34	.30	.28
10.0	.41	.33	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.37	.32	.27	.26





Guangdong Meide Testing Technology Co., Ltd.



5.6 WEC AND CCEC

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.279	.159	.050	.272	.155	.049	.259	.149	.047	.247	.142	.046	.236	.137	.044	
2.0	.271	.148	.046	.265	.146	.045	.253	.141	.044	.242	.136	.043	.233	.132	.041	
3.0	.255	.136	.041	.250	.134	.040	.239	.130	.039	.230	.126	.039	.221	.123	.038	
4.0	.238	.124	.036	.233	.122	.036	.224	.119	.036	.216	.116	.035	.208	.113	.034	
5.0	.222	.113	.033	.218	.112	.033	.210	.109	.032	.202	.107	.032	.195	.104	.031	
6.0	.207	.104	.030	.204	.103	.030	.196	.101	.029	.190	.099	.029	.184	.097	.029	
7.0	.194	.096	.027	.191	.095	.027	.184	.093	.027	.178	.091	.027	.173	.090	.026	
8.0	.182	.089	.025	.179	.088	.025	.173	.086	.025	.168	.085	.025	.163	.084	.024	
9.0	.171	.083	.023	.168	.082	.023	.163	.081	.023	.158	.079	.023	.154	.078	.023	
10.0	.161	.077	.021	.159	.077	.021	.154	.075	.021	.150	.074	.021	.146	.073	.021	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.178	.156	.137	.152	.134	.118	.104	.092	.081	.060	.053	.047	.019	.017	.015		
2.0	.169	.132	.101	.145	.114	.087	.099	.079	.061	.057	.046	.036	.018	.015	.012		
3.0	.162	.114	.076	.139	.099	.066	.095	.068	.046	.055	.040	.027	.018	.013	.009		
4.0	.154	.101	.060	.132	.087	.052	.091	.061	.037	.053	.036	.022	.017	.012	.007		
5.0	.147	.090	.048	.126	.078	.042	.087	.055	.030	.050	.032	.018	.016	.010	.006		
6.0	.140	.082	.040	.120	.071	.035	.083	.050	.025	.048	.029	.015	.016	.010	.005		
7.0	.134	.075	.034	.115	.065	.030	.079	.046	.021	.046	.027	.012	.015	.009	.004		
8.0	.127	.069	.029	.110	.060	.025	.076	.042	.018	.044	.025	.011	.014	.008	.004		
9.0	.122	.064	.026	.105	.056	.022	.073	.039	.016	.042	.023	.009	.014	.008	.003		
10.0	.116	.060	.023	.100	.052	.020	.069	.037	.014	.040	.022	.008	.013	.007	.003		



Guangdong Meide Testing Technology Co., Ltd.



5.7 UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	31.9	33.4	32.2	33.6	33.8	31.5	33.0	31.8	33.2	33.4
3H	32.9	34.3	33.2	34.5	34.7	32.5	33.8	32.8	34.0	34.3
4H	33.2	34.5	33.5	34.7	35.0	32.6	33.9	32.9	34.1	34.4
6H	33.3	34.5	33.7	34.8	35.1	32.6	33.8	32.9	34.1	34.3
8H	33.3	34.5	33.7	34.8	35.1	32.6	33.7	32.9	34.0	34.3
12H	33.3	34.4	33.7	34.7	35.0	32.5	33.6	32.9	33.9	34.2
4H 2H	32.4	33.6	32.7	33.9	34.2	32.0	33.3	32.3	33.5	33.8
3H	33.5	34.6	33.9	34.9	35.2	33.1	34.2	33.5	34.5	34.8
4H	33.9	34.9	34.3	35.2	35.6	33.3	34.3	33.7	34.6	35.0
6H	34.1	35.0	34.5	35.3	35.7	33.4	34.3	33.8	34.6	35.0
8H	34.1	34.9	34.5	35.3	35.7	33.4	34.2	33.8	34.6	35.0
12H	34.1	34.9	34.5	35.2	35.6	33.4	34.1	33.8	34.5	34.9
8H 4H	34.0	34.8	34.4	35.2	35.6	33.4	34.3	33.9	34.6	35.0
6H	34.2	34.9	34.7	35.3	35.8	33.6	34.2	34.0	34.6	35.1
8H	34.3	34.9	34.8	35.3	35.8	33.6	34.2	34.1	34.6	35.1
12H	34.3	34.8	34.8	35.3	35.8	33.6	34.1	34.1	34.6	35.0
12H 4H	34.0	34.7	34.4	35.1	35.5	33.4	34.2	33.9	34.6	35.0
6H	34.2	34.8	34.7	35.3	35.7	33.6	34.2	34.0	34.6	35.0
8H	34.3	34.8	34.8	35.3	35.7	33.6	34.1	34.1	34.6	35.0
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.3					+ 0.4 / - 0.4				
1.5H	+ 0.3 / - 0.5					+ 0.3 / - 0.6				
2.0H	+ 0.4 / - 0.4					+ 0.3 / - 0.8				

CIE Pub.117, 263.4 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = -4.6$)



Guangdong Meide Testing Technology Co., Ltd.



5.8 UTILIZATION FACTORS TABLE


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	59	48	41	58	47	41	57	47	41	34
0.80	69	58	51	68	58	51	67	57	50	44
1.00	78	68	61	77	67	60	75	68	60	53
1.25	85	75	69	84	75	68	81	73	68	61
1.50	90	81	75	89	80	74	86	78	73	66
2.00	97	89	83	95	88	82	92	86	81	73
2.50	101	94	88	99	92	87	95	90	85	77
3.00	104	98	93	102	96	92	98	93	89	81
4.00	108	102	98	105	101	97	101	97	94	86
5.00	110	105	102	107	104	100	103	100	97	88
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004				Suspended				SHRNOM = 1.25		



Guangdong Meide Testing Technology Co., Ltd.




5.9 ISOCANDELA DIAGRAM





5.10 AAI Figure






Guangdong Meide Testing Technology Co., Ltd.



5.11 ISOLUX DIAGRAM






Guangdong Meide Testing Technology Co., Ltd.



5.12 Planar Illuminance Curve





Guangdong Meide Testing Technology Co., Ltd.



5.13 Luminous Distribution Intensity Data

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8			
5	92.0	94.0	93.1	95.5	94.4	92.5	92.5	91.8	91.5	94.9	92.9	96.5	91.2	93.9	93.8	95.0			
10	90.3	92.5	93.7	94.8	91.0	93.1	90.8	95.1	91.4	92.7	91.5	94.8	92.2	95.0	101	93.1			
15	91.5	92.4	95.1	93.8	88.9	90.9	92.3	89.1	87.8	91.8	90.9	96.3	91.8	92.3	92.8	94.4			
20	89.8	90.7	93.2	91.8	88.0	87.5	92.6	86.8	86.2	92.2	90.9	94.8	91.7	91.3	92.9	92.8			
25	87.3	89.8	93.0	87.3	82.5	86.8	87.1	84.1	84.2	86.7	89.0	92.3	88.2	90.2	90.7	93.9			
30	85.0	86.9	88.9	86.3	80.7	84.5	83.5	82.0	78.3	83.0	87.0	90.1	86.6	87.4	87.3	88.9			
35	79.6	80.5	83.1	79.0	77.2	81.2	77.7	76.0	75.2	76.3	83.8	83.1	82.2	83.6	85.1	84.6			
40	75.3	75.8	77.5	71.8	71.6	70.9	73.2	69.3	68.3	71.1	80.1	78.4	75.6	77.7	79.2	76.0			
45	68.8	68.0	70.1	70.0	61.0	63.6	66.1	61.5	62.0	66.5	71.2	69.3	68.1	70.9	72.2	70.2			
50	60.0	61.2	61.1	59.3	55.0	55.8	55.7	53.9	51.6	57.5	60.5	60.5	57.8	61.3	64.1	60.9			
55	50.8	53.4	53.0	50.3	44.9	46.2	47.5	46.5	43.4	48.1	50.4	53.3	50.4	52.2	53.8	51.1			
60	41.0	42.6	41.5	41.3	35.9	37.1	35.0	36.2	34.8	38.8	40.2	42.8	40.1	40.7	43.2	42.6			
65	29.2	31.3	29.8	30.1	27.5	26.6	26.5	26.0	25.2	27.7	28.6	30.5	28.1	30.6	32.6	30.9			
70	20.4	20.8	19.8	20.2	17.9	17.7	16.9	16.7	17.0	19.0	19.8	19.8	18.7	19.2	21.0	21.9			
75	12.2	12.6	12.9	9.18	7.42	7.41	10.3	9.61	9.12	11.1	11.9	10.08	8.20	9.54	12.0	12.9			
80	5.47	5.68	4.57	4.23	3.70	3.72	3.51	4.25	4.10	4.97	5.12	1.57	1.71	1.70	4.10	6.21			
85	1.59	1.22	1.32	1.24	1.28	1.19	0.83	0.64	0.26	0.36	0.00	0.00	0.00	0.00	0.00	0.18			
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
145	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
155	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			



Guangdong Meide Testing Technology Co., Ltd.



6.Photo of sample




Figure 1




Figure 2

***** END OF THE TEST REPORT*****